



INNOVATIVE DESIGN  
for wheel quick positioning

NO CONTACT  
with the rim



RELIABLE AND FAST CLAMPING  
thanks to the innovative coupling mechanism

## FEATURES

**Fastening to the wheel:** no contact with the rim to prevent any damage.

**Quick:** quick lever-operated mounting and demounting, without toothed gears.

**Self-centering:** the synchronous opening and closing mechanism allows the central pin to be always aligned with wheel centre.

The rollers integrated inside jaws allow greater smoothness and mounting ease.

**Runout:** suitable for thrust compensation procedure of 3D aligners (\*).

**Lightweight and ergonomic:** the innovative design and low weight make it easy to handle and operate.

\* Refer to the wheel aligner catalogue to check for compatibility.

## OPTIONAL ACCESSORIES



### MULTI-PURPOSE TROLLEY

Clamp holder multi-purpose trolley and additional jaws.



### CLAMP HOLDER

Clamp holder set for wall mounting with support for additional jaws.



### VAN EXTENSIONS

Extension set for use with vans.



### XL EXTENSIONS

Set of XL extensions for wheel diameter from 32" to 39".

## TECHNICAL SPECIFICATIONS

Compatibility	3D aligners (*)
Wheel diameter	19" to 39"
Rim diameter	10" to 30"

### Wheel arch protection included

The set of supplied extensible jaws allows working on wheel diameter from 19" to 32".

\* Refer to the wheel aligner catalogue to check for compatibility.