PDCH 55C PDCH 45C





C-LINE Lifting equipment

Electro-hydraulic two post lifts with top connections.

Possibility of installation in symmetrical or asymmetric version.





Standard height of two-post connection: 4,050 mm.

Available versions (with optional column extension set):

- V: Specific for vans (Height of two-post connection: 4,620 mm).
- XV: Specific for vans and very high vehicles, extra-high version (Height of two-post connection: 5,220 mm).



- Internally reinforced column structure for little bending and internal cable guiding.
- Electro magnet safety release 24V.
- Rubber door protections. Toothed sector arm rotation stop system.
- Four three-section symmetrical arms.





Supplied accessories

All models complete with:

Safety stop-bar included as standard. Two set of extension pads.











Technical	Data


_			
Model	PDCH 45C	PDCH 55C	
Lift capacity	4500 kg	5500 kg	
Lifting time	45	45 s	
Three phase motor	400/230V - 3kW -	400/230V - 3kW - 3Ph - 50/60Hz	
Single phase motor	230V - 3kW - 1	230V - 3kW - 1Ph - 50/60Hz	
Max. lifting height	2062 mm		
Max. locking position	1957 - 2037 mm		
Lift minimum height	115 r	115 mm	
Height connection	4050/4620/5520 mm		


- A Column extension set
- **B** 8-43300021 Set of 4 extension for pads, H=35 mm
- **C** 8-43300014 Set of 4 extension for pads, H=80 mm
- **D** 8-43300015 Set of 4 extension for pads, H=140 mm
- **8-43300016** Set of 4 adapters for Mercedes Sprinter

Overall Dimensions









The manufacturer reserves the right to modify the features of its products at any time.









夏鲁