



SICE
AUTOMOTIVE EQUIPMENT

**FIT LINE
FL 61X**

DIGITAL WHEEL BALANCER

**Developed to ensure reliability,
ease of use and speed in the daily
operations of workshops and tyre
specialists.**



- HIGH-VISIBILITY DIGITAL DISPLAY
- AUTOMATIC MEASUREMENT SYSTEMS
- ERGONOMIC WORKSTATION
- IDEAL FOR STEEL AND ALLOY WHEELS ON PASSENGER CARS, INCLUDING SUVs, MOTORCYCLES AND SCOOTERS

NEW

KEY FEATURES

DIGITAL DISPLAY & ERGONOMIC WEIGHT TRAY

Clear and intuitive interface with a **high-brightness display**, designed to ensure immediate reading of balancing data and improve speed and user experience. The structure, made of durable materials, provides a **practical and well-organised space for counterweights and accessories**, optimising workstation management.



QP QUICK PROGRAM

The **QP (Quick Program)** automatically detects **distance and diameter (up to 26")** and selects the correct balancing programme.

Adhesive weights can be applied:

- manually at **12 o'clock or 6 o'clock**
- in assisted **mode via integrated weight holder clip**
- with laser pointer support at **6 o'clock** (optional)



CLIP

LASER

ES 6 D – RIM WIDTH MEASURING DEVICE (optional)

Enables **automatic rim width measurement**, reducing operation time and simplifying the balancing process.





FOOT-OPERATED PARKING BRAKE (optional)

Allows **quick wheel locking**, simplifying positioning operations.



LASER & LED KIT (optional)

Illuminates the inner rim area, improving visibility during cleaning and weight application.

The **Laser Line pointer** precisely indicates the application position at **6 o'clock**.



WHEEL GUARD

The machine is supplied with a **wheel guard and automatic spin cycle**.

Also available in a **guardless configuration**, where permitted.



CCK PANEL ON REQUEST (optional)



SICE
AUTOMOTIVE EQUIPMENT

**FIT LINE
FL 61X**

TECHNICAL DATA

Machine dimensions	1270x1704x1089 50"X67"X42,9"
Equipment weight	127 Kg 280 lbs
Rim diameter	10"-26" 1"-35"
Wheel width	1,5"-20" 38-508 mm
Max wheel diameter	44" 1118 mm
Max wheel weight	70 Kg 154 lbs
Power supply	115/230V 1Ph - 50/60Hz
Balancing speed	150 rpm
Motor power	250 W

SCOPE OF DELIVERY




Ø 42÷156 mm
(1,65" ÷ 6,14")

Cod. DPS000826_06/2026

RECOMMENDED ACCESSORIES



8-21100141
DX/CBF Centering device
for vans and SUVs with
centre hole Ø 117-173 mm



8-21900206/XX
CCK Colour panel kit
for grey chassis
RAL7040 (/39)

RAL 1003 3002 5002 5015



8-21100161/90
EL 80 E Wheel lifter



8-21900207
PB Foot-operated brake



8-21900209
ES 6 D Rim width measuring
device with support



8-21100238
LL Kit LED internal wheel
light + laser pointer