EXPORT GATALOGUE EFFECTIVE FROM MARCH 2025

MISCELLANEOUS AND ORIGINAL ACCESSORIES



REL. JULY 2025

COLOR TABLE

Standard		RAL 1007	Yellow	A = > /40
Optional		RAL 3002	Red	B => /16
Optional		RAL 5015	Blue	C => /25
Optional		RAL 9006	Light gray	D => /36
Main frame is al	ways d	ark grey RAL 70°	16	=> /34

NEXION SPA reserves the right to change the specifications of its products at any time without prior notice. The company declines all responsibility in the event of claims deriving from the use of non-original accessories or spare parts with consequent forfeiture of the EC declaration of conformity.



SUMMARY

AUXILIARY WHEEL LIFTERS	4
PARTNER 70	4
NITROGEN GENERATOR	5
N SERIES	5
N 300	5
N 500	5
N 1800	5
OPTIONAL ACCESSORIES FOR SERIE N	6
WHEEL WASHER	8
LS 850	8
OPTIONAL ACCESSORIES FOR LS 850	9
VULCANIZERS	11
SVP1	11
SVP2	11
SVP3	11
SVP4	12
SVP5	12
SVP5/L	12
OPTIONAL ACCESSORIES FOR VULCANIZERS	13
TYRE TEST TANKS	14
AL18	14
AL24	14
AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATION	15
A/C 1100 SERIES	15
A/C 1105 SERIES	16
A/C 1600 SERIES	17
A/C 1605 SERIES	18
OPTIONAL ACCESSORIES	19



PARTNER 70

Battery-Operated Wheel Lifter - it helps to easily and safely demount, move and mount the wheels of cars, SUVs and LT vehicles weighting up to 70kg



Code	Electric supply	Description	
8-21120020/64		PARTNER 70	

N SERIES







N 1800

Code	Electric supply	Description	
0-55401200/16		N 300 Nitrogen generator with capacity 3,0 Nm 3/h (3000 lit/h).	
0-55401300/16		N 500 Nitrogen generator with capacity 5,0 Nm 3/h (5000 lit/h).	
0-55401600/16		N 1800 Nitrogen generator with capacity 18,0 Nm 3/h (18.000 lit/h).	

OPTIONAL ACCESSORIES FOR SERIE N

Image	Description	Code
	WS Cyclonic condensate separator.	8-53600000
	AT Pipes take-up.	8-55600001
	PSG Professional inflating and deflating pistol.	8-55600002
	EC Inflating and deflating pistol, pressure gauge BAR G 1/4"	8-11100362



OPTIONAL ACCESSORIES FOR SERIE N

Image	Description	Code
	EC Inflating and deflating pistol, pressure gauge BAR and PSI G 1/4"	8-51120007
	NT Kit for measuring purity.	8-11600127
	Kit filter cartridges 3-5 Nm3/h.	8-55600023
	Kit filter cartridges 20 Nm3/h.	8-55600024
	Air contamination indicator.	8-55600025



LS 850

Dotazione









Code	Electric Supply	Description	
0-55400800/34	400V / 3Ph / 50Hz	LS 850 B with steel tank, without heater.	
0-55400700/34	400V / 3Ph / 50Hz	LS 850 P with steel tank and heater.	
0-55401500/34	400V / 3Ph / 50Hz	LS 850 T with stainless steel tank and heater.	

OPTIONAL ACCESSORIES FOR LS 850

Image	Description	Code
x2	RTP kit, replacing kit for drive roller.	8-55600026
x2	RSA kit, replacing kit for support roller.	8-55600027
	SLR Wheel Lifter.	8-51120005



OPTIONAL ACCESSORIES FOR LS 850

Image	Description	Code
	Set of granules for filling and replacement (15 kg.).	8-51100063
SUPER CLEAN SUPER CLEAN Manufacture Manuf	Non-foaming <i>liquid detergent</i> , 10 lt.	8-55600010
THE STATE OF THE S	VSS Ball faucet for water drainage.	8-55600019
1.5	RCS Elbow fitting for water drainage.	8-55600018









SVP₁

SVP2

SVP3

Code	Electric Supply	Description	
0-51400310/40	230V/1Ph/50-60Hz	SVP1 with manual lever operated plate clamping	
0-51400320/40	230V/1Ph/50-60Hz	SVP2 With air-operated closingmechanism, to repaire inner tubes and lightweigt tyres	
0-51400330/40	230V/1Ph/50-60Hz	SVP3 Strongly built and easy to use, ideal to repair inner tubes and light weight tyres 600W heating plate.	

VULCANIZERS







SVP4

SVP5

SVP5/L

Code	Electric Supply	Description	
0-51400340/40	230V/1Ph/50-60Hz	SVP4 Vulcanizer with double heating plate airoperated system to close the plates monitored by a pressure governor	
0-51400350/40	230V/1Ph/50-60Hz	SVP5 Vulcanizer with mechanically closed double heating plate.	
0-51400355/40	230V/1Ph/50-60Hz	SVP5/L Vulcanizer with mechanically closed double heating plate. Portable and easy to handle. Complete with 120 minutes timer. Two wide 600 W heating plates.	

OPTIONAL ACCESSORIES FOR VULCANIZERS Description Image Code Support stand 805420833



AL18







Code	Electric Supply	Description	
0-51400200/40		AL18 Air-operated with 6/8 bar operating pressure, complete with wheel holder lifting and lowering control. Maximum wheel diameter 800 mm. Maximum wheel width 320 mm.	
0-51410200/40		AL24 Complete with air filter, air-operated with 8 bar operating pressure. Maximum wheel diameter 1300 mm. Maximum wheel width 500 mm.	

AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATION

A/C 1100 SERIES



Code	Electric Supply	Description	
0-66500201/64	230V/1Ph/50-60Hz	A/C 1100 Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicle management, 192x64pixels LCD display, Wi-Fi/BT connection	
0-66500601/64	230V/1Ph/50-60Hz	A/C 1100P Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 192x64pixels LCD display, Wi-Fi/BT connection, printer included	



A/C 1105 SERIES



Code	Electric Supply	Description	
0-66500301/64	230V/1Ph/50-60Hz	A/C 1105 Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 192x64pixels LCD display, Wi-Fi/BT connection	
0-66500701/64	A/C 1105P Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicle management, 192x64pixels LCD display, Wi-Fi/BT connection, printer included		



A/C 1600 SERIES



Code	Electric Supply	Description	
0-66500401/64	230V/1Ph/50-60Hz	A/C 1600 Fully automatic Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display, Wi-Fi/BT connection	
0-66500801/64	230V/1Ph/50-60Hz	A/C 1600P Fully automatic Air Conditioning recharging station, R-134a refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display, Wi-Fi/BT connection, printer included	



A/C 1605 SERIES



Code	Electric Supply	Description	
0-66500501/64	230V/1Ph/50-60Hz	A/C 1605 Fully automatic Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display, Wi-Fi/BT connection	
0-66500901/64	230V/1Ph/50-60Hz	A/C 1605P Fully automatic Air Conditioning recharging station, R-1234yf refrigerant only, manual and automatic functions, recovery-recycle-recharge, hybrid vehicles management, 7" 800x480pixels TFT-LCD RBG display, Wi-Fi/BT connection, printer included	



OPTIONAL ACCESSORIES FOR AIR CONDITIONING SYSTEM DIAGNOSIS AND RECHARGE STATION

Image	Description	Code
	High/low pressure pipes kit, L=4,5 mt for, R1234yf refrigerant	8-66500010
	High/low pressure pipes kit, L=4,5 mt, for R134a refrigerant	8-66500011
	Leak detector with Nitrogen	8-66500209
	Leak detector kit including UV lamp and glasses only.	6019000305





